



30LB FELT PAPER 226

DESCRIPTION

F30-226 is an industry leading, superior quality "authentic" asphalt saturated organic felt underlayment. Manufactured to the highest specifications.

USES:

F30-226 authentic asphalt saturated organic felt underlayment is used as a breathable secondary weather resistant barrier when applied over the roof deck prior to the installation of the primary roofing product.

FEATURES AND BENEFITS:

- **Reliable:** Proven technology, successful on millions of structures for over a century.
- **Compatible:** Approved and recommended for use in all roofing applications.
- **Versatile:** Manufactured to perform in all climate conditions and all types of structures.
- **Easy to Apply:** No special fasteners required. (Note: Plastic cap nails help seal around nail holes.)
- **Cost Effective:** Convenient roll size, 200 sq ft. coverage with salvage edge, minimizes job loss and excessive waste.
- **Required:** Specified for use by architects, building code officials and primary roofing manufacturers. (Note: Approved underlayment is required to validate warranty on most all roofing systems.)
- **Permeable:** Breathable membrane to help prevent dry rot, mold, and other structural damages.
- **Walk-able:** Natural non-skid surface; ideal for steep slope roofing.
- **Durable:** Remains viable even after prolonged exposure. Minimum of 60 days in single ply and 6 months in two ply applications.
- **Eco-Friendly:** Organic dry felt is made from 100% post consumer recycled material and domestic asphalt from a local source. (Note: Leed points may be available.)

PRODUCT INFORMATION:

- Width: 39 3/8 Inches
- Coverage: 216 Sq. Ft.

APPROVALS & CERTIFICATIONS:

ASTM D 226 Type II
ASTM D 4869 Type IV
UL specifications for prepared roofing accessory



LIMITED WARRANTY AND DISCLAIMER:

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Perma-Tech Roofing Supply to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with Perma-Tech Roofing Supply warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: www.permatechroofing.com.