



## 40LB ORGANIC BASE SHEET

### DESCRIPTION

OBS40 is manufactured from superior quality organic felt that is saturated with asphalt and then coated on both sides with weathering grade asphalt and then covered on top with mineral surface fines to prevent sticking in the roll.

### USES

OBS40 base sheet can be used for commercial as well as residential roofing systems. OBS40 base sheet is applied over the flat roofing deck or insulation before the application of Built-Up Roofing systems. Follow building code and local amendments when installing OBS40. Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment.

### EXPOSURE

OBS40 can be left exposed for 180 days from date of application. It is the contractors responsibility to repair any areas where damage to underlayment has occurred due to "workbench abuse" prior to application of primary roofing material.

### TECHNICAL DATA

Typical Properties, 2.0 square roll

- Average Weight of Roll: 78 lbs
- Mass of Asphalt Saturant: 7.2 lbs/100 sq ft
- Mass of Desaturated Felt: 5.2 lbs/100 sq ft
- Saturation Efficiency (min) by Weight: 70%
- Breaking Strength at 77F (min)
- Machine Direction: 35 lbf/in
- Cross Direction: 20 lbf/in

### PRODUCT INFORMATION:

- Width: 39 3/8 in
- Length: 65 ft 10 in
- Coverage: 216 Sq. Ft.

### APPROVALS & CERTIFICATIONS:

ASTM D2626



### LIMITED WARRANTY AND DISCLAIMER:

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Perma-Tech Roofing Supply to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with Perma-Tech Roofing Supply warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: [www.permatechroofing.com](http://www.permatechroofing.com).